





Operational Hydrology

Assessment of current water resources for decision support in project management, flood or drought forecasting, or military operations.

CRREL's role:

- Research and support in cold regions
 - Develop new or improved techniques, models and data
 - Enhance understanding of complex problems





Snow Hydrology

Snow hydrology is the science of estimating the amount of snow water equivalent distributed across a watershed, and the volume and timing of run-off from the snow cover.

Involves:

- Snow Physics
- Snow Data
- Snowmelt modeling






Overview

- Snow Physics characteristics and formation
- Snow Data Collection
- Snow Modeling
- Operational examples:
 - Military Support
 - 3 Case Studies






Snow Crystal Formation




A-Axis Growth



Dendrite



Sectored Plate




Dendritic Sectored Plate

C-Axis Growth



Needle




Prism (Column)





Snow Pack Characteristics



Snow Pack Characteristics

- Snow Water Equivalent (SWE)
 - The height of water if a snow cover is completely melted, on a corresponding horizontal surface area.

• Snow Depth x (Snow Density/Water Density)






Density of Snow Cover

Snow Type	Density (kg/m³)	Snow Depth for One Inch Water
Wild Snow	10 to 30	98" to 33"
Ordinary new snow immediate after falling in still air	ly 50 to 65	20" to 15"
Settling Snow	70 to 90	14" to 11"
Average wind-toughened snow	v 280	3.5"
Hard wind slab	350	2.8"
New firn snow	400 to 550	2.5" to 1.8"
Advanced firn snow	550 to 650	1.8" to 1.5"
Thawing firn snow	600 to 700	1.6" to 1.4"



snow physics



Snow Pack Characteristics

• Liquid Water Content

Wetness, Percentage by volume

	Term	Remarks Approximate	Range
	Dry	Usually T $< 0^{\circ}$ C, but can occur at any temperature up to 0°C. Little tendency for snow grains to stick together.	0%
	Moist	T = 0°C. The water is not visible even at 10x magnification. Has a distinct tendency to stick together.	<3%
	Wet	T = 0°C. The water can be seen at 10x magnification by its miniscus between grains, but cannot be pressed out by squeezing snow (pendular regime).	3-8%
	Very Wet	T = 0° C. The water can be pressed out by squeezing snow, but there is an appreciable amount of air (funicular regime).	8-15%
US Army of Engine	•	T = 0°C. The snow is flooded with water and contains a relatively small amount of air.	>15% CRR

Snow Characteristics


- Temperature
 - Two basic situations:
 - Variation in temperature between the top of the snow pack and the ground
 - Temperature Gradient
 - Largely determined by thickness of snow pack and the mean snow surface temperature
 - » Base of snow pack is usually near 0°C
 - No temperature gradient
 - Isothermal





Snow Characteristics


• Diurnal Temperature Gradients







snow data collection




Snow Course Data



Chena Basin, Fairbanks, AK April 2011 Snow Course












snow data collection


0



М

snow data collection

Snow Course Sites in New England








Airborne Snow Survey Program

- Snow Water Equivalent (SWE) estimated from attenuation of naturally occurring terrestrial gamma radiation.
 - Typical flight line is 16 km long, measuring a ground swath 3000 m wide.
 - Measures average SWE over area of ~5 km²
 - 1800 flight lines throughout coterminous U.S.
 - Two twin-engine aircraft fly ~900 lines/year.






Airborne Snow Survey Program



Airborne Snow Survey Program



2,187 Flight Lines

31 States, 8 Provinces








snow data collection SNOW COURSE DATA NOHRSC Gamma Survey Real-Time maps of SWE/ Snow Course (various) Depth SWE **Snow Depth** HEC-HMS gridded input of snow conditions Comparison of real-time POINT DATA watershed SWE with NWS 1st Order Stations historical SWE **Snow Depth NWS** Cooperative Comparison of snow Precipitation **CWMS Database** Stations distribution maps with Temperature historical SNOTEL Stations Period of record updates to historical averages **Snow Properties** Real-time watershed SWE SCA **DISTRIBUTED DATA** SWE Sand Comment of the Sand Sand Sand Sand Tabular displays of SWE and NOHRSC NSA (1km) depth by watershed Satellite Data SSM/I (25 km) MODIS (500 m) AVHRR (1km)

Point Data

- Meteorological Stations
 - Snow Depth
 - <u>S</u>now <u>Water Equivalent (SWE)
 </u>
 - Snow Fall
 - Precipitation (under catch)











Point Data

• SNOTEL


- SWE
- Temperature
- Precipitation
- Snow depth
- Meteor burst telemetry







snow data collection



Satellite Snow Data

- Snow Water Equivalent Passive Microwave
 - Special Sensor Microwave/Imagers (SSM/I)
 - Advanced Microwave Scanning Radiometer-EOS (AMSR-E)
- Snow Covered Area Optical
 - Moderate Resolution Imaging Spectroradiometer (MODIS)
 - Advanced Very High Resolution Radiometer (AVHRR)
- New satellites every year






Satellite Passive Microwave

- Passive microwave sensors measure natural microwave emissions (brightness temperature) from the Earth's surface and atmosphere
 - Precipitation
 - oceanic water vapor
 - near-surface wind speed
 - soil moisture
 - snow cover
 - sea ice parameters
- Polar Orbiting
- Pros
 - Complete coverage of Earth twice per day
 - Can see through clouds and at night
 - Inexpensive
- Cons

Low resolution, 25 km grid cells Signal is impacted by wet snow/snow metamorphism


US Army Corps of Engineers





Passive Microwave Detection of Snow


- Microwave radiation from the soil and the snowpack is scattered by the snow grains
- The reduced brightness temperature detected by the sensor is a function of the snow depth and density
- For each 25 km² gridcell, a single brightness temperature is estimated
- Snow Depth Range
 - SSM/I: 0-40cm
 - AMSR-E: 0-100cm
- SWE = C(T37H T19H)







Optical Satellite Measurements of Snow Covered Area (SCA)




Remote Satellite Assessment of Snow Covered Area (SCA)

- <u>A</u>dvanced <u>Very High Resolution Radiometer (AVHRR)</u>
 - 1 km square pixel; can estimate sub-pixel snow coverage (0-100%)
 - Daylight only; cannot see through clouds; no information on SWE
 - Requires extensive in-house processing





snow data collection



Snow cover area (SCA) maps composited with color background, derived from NOAA AVHRR. SCA represented as gray shade from black to white. Clouds within maximum snow extent show as red.


Remote Satellite Assessment of Snow Covered Area (SCA)

- Moderate Resolution Imaging Spectroradiometer (MODIS)
 - 500 m square pixel
 - Daylight only, cannot see through clouds, no information on SWE
 - Automatic classification
 - http://nsidc.org/data/snowi/search.html





snow data collection



US Army Corps of Engineers


Estimating Watershed SCA

SCA estimates are important where:

- •No impact of elevation
- •During the ablation period
- •Snow exhibits spatial and temporal heterogeneity

Snow Distribution Great Plains - random tracks of episodic snowstorms with re-distribution by wind





snow data collection SNOW COURSE DATA NOHRSC Gamma Survey Real-Time maps of SWE/ Snow Course (various) Depth SWE **Snow Depth** HEC-HMS gridded input of snow conditions Comparison of real-time **POINT DATA** watershed SWE with NWS 1st Order Stations historical SWE Snow Depth **NWS** Cooperative Comparison of snow **CWMS Database** Precipitation Stations distribution maps with Temperature historical SNOTEL Stations Period of record updates to historical averages **Snow Properties** Real-time watershed SWE SCA DISTRIBUTED DATA SWE Tabular displays of SWE and NOHRSC NSA (1km) depth by watershed Satellite Data SSM/I (25 km) MODIS (500 m) AVHRR (1km)

NOAA's National Snow Analyses (NSA)

Multi-sensor Snow Observations Snow Modeling and Data Assimilation

Snow Information Products

Ground

Airborne

Satellite

US Army Corps of Engineers

Numerical Weather Prediction Model Forcings

Gridded Snow Characteristics

U.S.

1-km²

Hourly

Data Products
Interactive
Maps

Time Series
Plots

Text Discussions

CRREL

Snow Modeling Framework

Hourly Input
Gridded Data (1 km)

Temperature
Relative Humidity
Wind Speed
Solar Radiation
Atmos. Radiation
Precipitation
Precipitation Type

Static Gridded Data (1 km)

Soils Properties Land Use/Cover Forest Properties

US Army Corps of Engineers

Snow Energy and Mass Balance Model

Blowing Snow Model

Radiative Transfer Model

State Variables for Multiple Vertical Snow & Soil Layers Snow Water Equivalent Snow Depth Snow Temperature Liquid Water Content Snow Sublimation Snow Melt

Data Assimilation

Snow Observations

Snow Water Equivalent

Snow Depth


Snow Cover

NSA Product
Generation
Interactive Maps
Digital Data
Discussions

CRREL

3


CONUS Snow Distribution 12/28/06-2/28/07 NOAA's NSA








Estimating SWE




Estimating SWE

Estimating Watershed SWE















Estimating Watershed SWE Volumes

- •Point estimates of SWE interpolated using inverse distanced weighting
- Biased by SSM/I SWE
- •Multiplied by AVHRR SCA











Estimating Watershed SWE: SSM/I



Lake Superior Watershed SWE




Snowmelt Forecasting Modeling

- Forecast snowmelt
 - Near term (1-5 days) based on met forecasts
 - Middle term (5-10 days) based on met forecasts
 - Seasonal statistical or ensemble forecasts based on climatology or historical records





Complete Energy Balance Snow Models








of Engineers

Temperature Index Snow Models





Snow Modeling


- Energy Balance
 - Wind
 - Temperature
 - Water Vapor
 - Radiation (Net)
 - Precipitation
- Detailed (layered) snow pack


- Temperature Index
 - Temperature
 - Precipitation
- Cold Content, Liquid water content
- One layer snow
- Calibration required






Distributed Snow Modeling








Hydrograph

US Army Corps of Engineers


modClark Conceptual Model



Lagged by Travel Time



Distributed Hydrological Model




Operational Snow Hydrology Examples

- Chena River Basin, Fairbanks, AK
- Upper Helmand Watershed, Afghanistan
- Red River of the North, MN, ND
- Military Support






Chena River Basin, Fairbanks, AK







Chena River Basin, Fairbanks, AK




Geo-HMS

DEM

USGS National Elevation Data

- -2 arc-second (approx 60 m) resolution
- -Downloaded in GCS NAD83 projection
- -Re-projected to NAD27 Albers






Geo-HMS

Chena River Basin

-Area: 2053 mi²

-Elevation range: 400 - 4800 ft




Basin Attributes

			Longest					
		Area	flow path	Elevation at	Elevation at	Slope	Percent	Percent
Subbasin	Description	(mi2)	length (mi)	divide (ft)	outlet (ft)	(ft/ft)	Impervious	Permafrost
1	North Fork Chena River	345.9	34.3	4312.5	810.4	0.019	0%	53%
2	Middle Fork Chena River	539.4	57.3	4807.9	826.8	0.013	0%	54%
3	Two Rivers Local	49.2	16.2	2574.6	716.4	0.022	0%	42%
4	Above Hunts Creek Local	89.2	17.2	1906.8	659.5	0.014	0%	40%
5	South Fork Chena River	249.9	39.6	3096.6	675.9	0.012	0%	54%
6	Hunts Creek Local	69.4	13.4	2442.3	610.2	0.026	0%	45%
7	Above Moose Creek Dam Local	104.4	25.5	2094.1	481.7	0.012	1%	34%
8	Below Moose Creek Dam Local	7.4	2.1	521.7	475.7	0.004	0%	3%
9	Little Chena	372.1	40.2	2905.8	495.4	0.011	0%	39%
10	Upper Fairbanks Local	168.1	38.2	1312.2	446.2	0.004	20%	5%
11	Lower Fairbanks Local	58.0	14.3	1355.0	400.3	0.013	35%	4%








Landuse by subbasin (AK NLCD, 2001)

Landuse	1	2	3	4	5	6	7	8	9	10	11
Barren Land	1%	1%	0%	0%	0%	0%	0%	0%	1%	1%	1%
Cultivated Crops	0%	0%	0%	0%	0%	0%	0%	0%	0%	1%	1%
Deciduous Forest	13%	15%	42%	37%	21%	22%	31%	53%	25%	28%	25%
Developed, High Intensity	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	2%
Developed, Low Intensity	0%	0%	0%	0%	0%	0%	0%	2%	0%	10%	23%
Developed, Medium Intensity	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	3%
Developed, Open Space	0%	0%	0%	0%	0%	0%	1%	0%	0%	9%	9%
Dwarf Shrub	2%	3%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Emergent Herbaceous Wetlands	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Evergreen Forest	50%	54%	36%	38%	61%	57%	36%	21%	45%	25%	17%
Mixed Forest	3%	3%	6%	11%	5%	10%	11%	9%	14%	4%	3%
Open Water	0%	0%	1%	1%	0%	1%	1%	2%	0%	2%	3%
Shrub/Scrub	27%	23%	11%	5%	7%	0%	3%	2%	7%	1%	1%
Woody Wetlands	2%	1%	4%	9%	4%	10%	15%	11%	6%	18%	10%
Other	1%	1%	0%	0%	0%	0%	0%	0%	0%	0%	1%





Soil Layers	Hydraulic Conductivity	Depth (in)	Notes
Fairbanks Organic Soil	High (0.5 – 20 in/hr)	10-30	Active layer, thaws immediately after snowmelt, saturation is function of time of year
Mineral Soil	Low (0.001 – 0.01 in/hr)	100+	Low permeability, long lag time




Soil Data Sources

- STATSGO, 2002
- Bolton, Dynamic Modeling of the Hydrologic Processes in Areas of Discontinuous Permafrost, 2006
- Kane, Plot Measurements of Snowmelt Runoff for Varying Soil Conditions, 1984



HMS Project Setup



Basin Model

Transform Method: Clark Unit Hydrograph


$$t_c = 21.3L_L A^{-0.1} S^{-0.2}$$


Baseflow Method: Recession $Q_t = Q_o K^t$

Loss Method: Soil Moisture Accounting

Routing Method: Muskingum-Cunge 8 point


Basin	t _c (hrs) (Williams)
1	10.2
2	17.7
3	5.7
4	6.3
5	13.5
6	4.4
7	9.4
8	1.3
9	13.2
10	16.6
11	5.6











Gage	ID	Elev (ft)	Data Available	Date Start	Date End
Fairbanks International Airport	FIA	453	SWE, P, T	Oct-82	Jun-08
Little Chena Ridge	AAE	2000	SWE, P, T	Oct-81	Current
Mt Ryan	AAF	2800	SWE, P, T	Oct-81	Current
Monument Creek	AAG	1850	SWE, P, T	Oct-80	Current
Munson Ridge	AAH	3100	SWE, P, T	Oct-80	Current
Tuechet	AAI	1640	SWE, P, T	Oct-81	Current
Upper Chena	AAJ	2850	SWE, P, T	Oct-87	Current
Chena River at Two Rivers	AAK	720	Q, P, T	Oct-67	Current
Chena River bl Hunts Creek	AAN	638	Q, P, T	Oct-91	Sep-09
Chena River bl Moose Dam	AAM	490	Q, P, T	Aug-79	Oct-08
Eittle Chena River nr Fairbanks	AAL	460	Q, P, T	Aug-96	Current
Chena River at Fairbanks		423	Q	Aug-47	Current






Model Calibration and Validation


- Calibration
 - 1994
 - 2008
 - 2009
- Validation
 - 1967
 - 1992
 - 1995







Model Calibration – June 2009









Operational Forecasting








Upper Helmand Basin, Afghanistan

Upper Helmand Watershed, Afghanistan Area: 47,000 km²




- Irrigation
- Water supply
- Flood reduction
- Power generation






GARDANDEWA




Arid country

30

- Limited data sources
- Floods/Droughts occur with little warning




Study Location




Snow Hydrology Model

- Hydrologic Model
 - Distributed 1 km
 - Temperature index snow model
 - HEC-HMS
- 6 winter seasons
 - 01 OCT 30 JUN
 - -2004-2009
- Model Input
 - Temperature
 - Precipitation









Snow Model - Data

• Precipitation Data

- Limited gage data
- TRMM 3B42 precipitation
- Resampled to 1km² grids









US Army Corps of Engineers

Snow Model - Calibration



Snow model calibration

- Snow model parameters were calibrated by comparing results spatially against SCA imagery
- High-resolution SCA imagery available from 2006-2009
- $R^2 = 0.86$
- Nash-Sutcliffe efficiency = 0.78





Snow Hydrology Model

Error Matrix Analysis:

- For each image, each pixel was classified as both the model and imagery containing snow, the model or the imagery containing snow but not the other, or neither containing snow.
- An overall accuracy of 85% is considered a reasonable match for error matrix analysis


2006-07


2006-07 Snow **Snow Model** No Snow


SCA Imagery

Snow	No Snow	_
257609	54672	312281
19508	256006	275514
277117	310678	587795

overall accuracy:







AVHRR only


Snow Model only

clouds





Results – SWE Comparison






$$R^2 = 0.53$$

Nash-Sutcliffe efficiency = 0.20 (model as



Reservoir Model

- Reservoir Data available:
 - Monthly reservoir levels, 1998 through present
 - Daily reservoir levels, 2006-07 and 2008-09
 - Elevation-Discharge relationship, includes
 - Irrigation withdrawals
 - Hydropower withdrawals
 - Spillway curve
 - Elevation Area Storage relationship











Hydrologic Model



Using AMSR-E as initial conditions




Observed Storage (10⁷ m³)





AMSR-E signal observations



Operational Forecasting








Red River Basin, MN, ND



Red River Basin, MN, ND 2009 snowmelt flood





US Army Corps of Engineers



of Engineers

Red River Basin, MN, ND 2009 snowmelt flood



Red River snow model

Red River Basin, MN, ND 2009 snowmelt flood





Red River Basin, MN, ND 2011 snowmelt flood


http://www.ndsu.edu/fargoflood/snowcover 2011/js movie.html

http://www.ndsu.edu/fargoflood/stages_2011/fargo_flood.html



Red River snow model

Operational Forecasting



Operational Support:

For the past 6 winter seasons we have provided bi-weekly assessments of the snowpack to U.S. Military personnel in Iraq and Afghanistan. This year Pakistan was also included.

Mission Relevance:

- Operation planning
- Supplies/Transport
- Flood forecasting
- Water supply








Clients

- Marine Corps Intelligence Agency
- American Embassy in Iraq
- Iraq Ministry of Water
- U.S. Central Command
- US Army 82nd Airborne Division
- US Navy
- US Air Force, AFWA
- Canadian Forces
- British Forces
- NATO
- USGS
- USDA
- USAID
- Dept of Disaster Response
- National Geospatial-Intelligence Agency
- German Embassy
- Academic Institutions
- And others



US Army Corps of Engineers






Application:

- The snow assessments use satellite imagery to analyze the snowpack.
- Assessments are sent by email every two weeks starting in November and going through May.

Each assessment includes:

- Snow covered area (SCA) map
- SCA by Elevation Band
- Snow Water Equivalent (SWE) charts
- General assessment of snowpack and flood risk
 - Summary of SCA and SWE data
 - Comparison to previous assessments
 - Summary of meteorological data
 - Flood risk assessment



Additional Product:


shapefiles


us Google earth snow cover
of Engineers




Snow Covered Area Map

- Advanced Very High Resolution Radiometer (AVHRR) / Moderate Resolution Imaging Spectroradiometer (MODIS)
- Algorithms developed to remove clouds










SCA by Elevation Band

Euphrates River Watershed in Turkey

Elevation	Area	SCA (km²)						
Band (m)	(km²)	29-Oct-07	12-Nov-07	26-Nov-07	8-Dec-07	24-Dec-07	7-Jan-08	21-Jan-08
0-500	8025	0	0	0	0	0	0	0
501-1000	31215	0	10	5	8	13	3676	1454
1001-1500	25838	0	2660	309	1906	3787	21215	16161
1501-2000	37295	0	18721	5517	16973	29524	36880	34611
2001-2500	15438	13	13211	9204	8161	15075	15396	15208
2501-3000	3811	160	2951	3382	1967	3765	3806	3806
3001-3500	260	1	103	239	185	254	260	260
3501-4000	3	0	0	3	0	2	3	3

^{*} The SCA is potentially under-represented because significant portions of these elevation bands were obscured by cloud cover.









Snow Water Equivalent Charts

- Special Sensor Microwave/Imager (SSM/I)
- Relative volume of SWE



Pakistan Meteorological Data






Limited air temperature (C) and precipitation (mm) data were obtained from the National Climatic Data Center (http://www.ncdc.noaa.gov.

Station: Drosh, Kabul Watershed, elevation 1465m Station: Murree, Lower Indus Watershed, elevation 2127m Station: Peshawar, Kabul Watershed, elevation 360m



Drosh Temperature Comparison



US Army Corps of Engineers

Historical data obtained from the National Climatic Data Center, 1957

Summary Operational Snow Melt Hydrology

- Depends on data from many sources:
 Course, point, distributed
- Watershed SWE: GIS to combine course, point, and distributed data
- Forecasting
 - Models, meteorology, climatology



